

R-A90S

6/5/4/3 Channel Amplifier with Staggered Power







- CHANNEL-1/2



APPLICATION GUIDE

THE JOURNEY TO ALPINE SOUND

Since 1978, Alpine has challenged the status quo

by creating innovative products that transform the invehicle entertainment experience. Our approach to sound reproduction strikes a chord with music lovers from all walks of life and motivates us to stay ahead of the curve by offering a unique upgrade path for the Journey to Alpine Sound.

ALPINE'S LEGENDARY

R-SERIES SOUND

Alpine's R-Series line of speakers, subwoofers, and amplifiers have a heritage of sound quality that can be heard from a block away. Known as the "Loud and Fun" sound system, R-Series products are designed to be played loud yet still deliver a dependable performance and accurate sound reproduction.

R-A90S PRODUCT OVERVIEW

Immerse Yourself in Alpine Sound with the Hi-Res R-A90S 6-Channel Power Amplifier. With the highest power output in its category, you'll hear the hair-raising details of your music with the most accurate sound reproduction for music that stays true to the artist's intention.

STAGGERED POWER

The most versatile amplifier in its class, the R-A90S has a staggered power channel layout that has double the amount of power on the 5th and 6th channels. With built-in bandpass, high pass, or low pass, the R-A90S can be used in various layouts for ultimate sound system flexibility.

ACCURATE IMAGING

The R-A90S has a smart and simplified circuit design along with dual post-filter feedback loops that correct internal noise and minimize phase shift. With the lowest phase shift of its kind, the R-A90s can deliver a proper center sound stage for more accurate music reproduction.

HI-RES SOUND

With the highest power output in its category, the R-A90S drives power to your sound system to create a big dynamic music range for the listener, reproducing high-frequency sounds up to 45k Hz for Hi-Resolution sound.




TECH SPECS

• Hi-Resolution Audio Compliant (40k Hz) • CTA-2006 • Alpine's Class D Amplifier Circuit 75W x 4 + 150W x 2 (4Ω, 14.4V, < 1% THD +N) • 100W x 4 + 250W x 2 (2Ω, 14.4V, < 1% THD +N) • Bridged: 200W x 2 + 500W x 1 (4Ω, 14.4V, < 1% THD +N) • S/N > 85dB (ref. 1W into 4Ω) • THD + N < 0.03% (ref. 10W into 4Ω) • Frequency response: 10-45kHz (0/-3dB) • Damping factor > 500 RUX-KNOB.2 Remote Bass Control Knob ready (sold separately)

Hi-Res

AUDIO







Resonanced Stars

СН. З

75W

R-S65.2













www.alpine-usa.com

